

Abrazaderas de reparación de fundición maleable DS



Para tubos de acero:

DIN EN 10255 (antes DIN 2440/2441), DIN 2442 y DIN 2448/DIN 2458 fila 1, ISO 65



- Para conducciones de: Agua
- Temperatura: Agua hasta +90 °C
- Medidas: 1/2" - 4"
- Presión de trabajo: Agua PN 16

Diámetro nominal	Código artículo	uni. caja
1/2"	01.252.28.01	5
3/4"	01.252.28.02	10
1"	01.252.28.03	10
1 1/4"	01.252.28.04	5
1 1/2"	01.252.28.05	3
2"	01.252.28.06	3
2 1/2"	01.252.28.07	
3"	01.252.28.08	
4"	01.252.28.09	

Características:

DN	Tubo de acero	[mm]	Peso [kg]	Dimensiones		
	Ø exterior [pulgadas]			~A [mm]	~B [mm]	~C [mm]
15	1/2"	21,3	1,3	134	45	84
20	3/4"	26,9	1,4	134	50	88
25	1"	33,7	1,65	134	57	98
32	1 1/4"	42,4	1,8	134	70	105
40	1 1/2"	48,3	2,0	134	75	112
50	2"	60,3	2,2	134	90	122
65	2 1/2"	76,1	2,6	134	105	139
80	3"	88,9	2,7	134	115	155
100	4"	114,3	3,5	134	140	194

Medidas Ø 1/2" - 4"

