



Art. No. 8341

DESCRIPCIÓN: Enlace 3 piezas M/H  
DESCRIPTION: M/F 3 pieces union

REVISIÓN / UPDATE 2: 21.07.2015

■ **MATERIALES:**

Cuerpo de acero inoxidable austenítico AISI316  
(UNE EN10213-4 / DIN 1.4408)

■ **LÍMITES TÉCNICOS:**

Temperatura de trabajo: -20°C - 200°C  
PN-10 bar (150 PSI)

■ **CARACTERÍSTICAS:**

Medidas de acuerdo con ISO4144  
Roscas BSP por CNC  
Roscas de unión de acuerdo con ISO 7/1 (DIN 2999 / BS 21)  
Proceso de microfundición en cera

■ **UTILIZACIÓN:**

Industria química, industria petroquímica y gas natural, industria alimentaria, entornos industriales de medios corrosivos y temperaturas extremas...  
Conducción de fluidos, calderas, condensadores, intercambio de calor, reactores...

■ **COMPONENTS:**

Body in austenitic stainless steel AISI 316  
(UNE EN10213-4 / DIN 1.4408)

■ **TECHNICAL LIMITS:**

Working temperature: -20°C - 200°C  
PN-10 bar (150 PSI)

■ **FEATURES:**



Dimensions according to ISO 4144  
BSP threads by CNC  
Joining threads according to ISO 7/1 (DIN 2999 / BS 21)  
Investment casting through in-house wax

■ **USE:**

Chemical, petrochemical and natural gas and food processing industries, corrosive industrial environments and extreme temperatures...  
Fluid handling, boilers, condensers, heat exchangers, reactors...

Código	DT.			A	B	L1	L2	M	Peso (g)	Perfil
Code									Weight (g)	Profile
8341-008	1/4"	250	10	16,5	29	33,5	10,5	13,5	73	Octogonal
8341-010	3/8"	160	10	20	34	36,5	11	15	106	Octogonal
8341-015	1/2"	100	10	24,5	37	39,5	14,5	16	145	Octogonal
8341-020	3/4"	60	10	30	44	42,5	15,5	17	206	Octogonal
8341-025	1"	45	5	37	52,5	50	18	20	331	Octogonal
8341-032	1 1/4"	20	5	46,5	63	54	20,5	22	492	Octogonal
8341-040	1 1/2"	15	5	53	70	58	20,5	24	620	Octogonal
8341-050	2"	10	1	65	84	65	25	27	958	Octogonal
8341-065	2 1/2"	8	1	82	101,5	75	27	29,5	1.413	Decagonal
8341-080	3"	6	1	95,5	118	83	30	31	2.023	Decagonal
8341-100	4"	4	1	121,5	148,5	110	36	34	3.690	Decagonal

Dimensiones en milímetros / All dimensions in millimeters.



Business Key, S.L. se reserva el derecho de modificar en parte o en su totalidad las características de sus productos sin previo aviso.  
Business Key, S.L. keeps the right to modify in part or totally the characteristics of its products without previous notice.



Para prevenir roturas, accidentes o daños severos, NO USAR este producto fuera de los límites técnicos y sus aplicaciones. Las normas locales pueden regular el uso de este producto.

To avoid abnormal operation, accidents or serious injury, DO NOT use this product outside of the specification range. Local regulations may regulate the use of this product.